

## Thermostatic Water Bath

**BMP 60** 



## Specially designed for serology

Ideal for modern laboratories, our serological bath is available in 2 volumes; 3 and 6 litres, and consists of a transparent plexiglass and a control interface via a button. This makes it very easy to use and set the ambient temperature between 7°C to 60°C.

PERFORMANCE	
Ambient temperature range	7°C to 60°C
Factory preset	37°C and 56°C
Capacity	6L
<b>♥</b> WARRANTY	
Parts	2 vears





## **Technical Specifications**

SEROLOGIC WATER BATH		
MODEL	BMP 60	
<b>≡</b> GENERAL SPECIFICATIONS		
Capacity (net)	6 liters	
Temperature Range (ambient)	7°C to 60°C	
Construction	Polycarbonate frame	
External Dimensions (W x H x D)	370 x 150 x 210 mm	
Internal Dimensions (W x H x D)	290 x 110 x 190 mm	
Weight (gross)	4kg	
Weight (net)	2kg	
Factory Setpoint	37°C and 56°C	
Water lack safety	Yes	
Warranty	2 years	
F ELECTRICAL DATA		
Power supply	230V ~ +/-10%, 50 Hz	
Energy consumption	250 W	
O COMPLIANCE		
Device complies with CE specification	s	
→ OPTIONS		

Polycarbonate lid

2 racks for 60 tubes diam. 14mm

Thermometer

<sup>\*</sup> Cleaning and decontamination with detergents and antimicrobials used in hospitals (Ammonium quaternary / except pure bleach)